

WKT SEALING COMPOUND

CONSUMPTION CALCULATOR 570 ml cartridges

Number of cartridges (570 ml) required per qm Deck														
		Measures of the joint												
		Width ▶		4 mm			5 mm			6 mm			8 mm	
				0.012 ft			0.015 ft			0.018 ff			0.024 ft	
Depth ▶				6 mm	8 mm	10 mm	6 mm	8 mm	10 mm	6 mm	8 mm	10 mm	10 mm	12 mm
				0.018 ft	0.024 ft	0.030 ft	0.018 ft	0.024 ft	0.030 ft	0.018 ft	0.024 ft	0.030 ft	0.030 ft	0.030 ft
Width of the Planks ▶	30 mm	0,090 ft	1.2	1.7	2.1	1.5	2.0	2.5	1.8	2.3	2.9	-	-	
	35 mm	0,105 ft	1.1	1.4	1.8	1.3	1.8	2.2	1.5	2.1	2.6	-	-	
	40 mm	0,120 ft	1.0	1.3	1.6	1.2	1.6	2.0	1.4	1.8	2.3	-	-	
	45 mm	0,135 ft	0.9	1.1	1.4	1.1	1.4	1.8	1.2	1.7	2.1	-	-	
	50 mm	0,150 ft	-	-	-	1.0	1.3	1.6	1.1	1.5	1.9	2.4	2.9	
	60 mm	0,180 ft	-	-	-	0.8	1.1	1.4	1.0	1.3	1.6	2.1	2.5	
	70 mm	0,210 ft	-	-	-	0.7	0.9	1.2	0.8	1.1	1.4	1.8	2.2	
	80 mm	0,240 ft	-	-	-	-	-	-	0.7	1.0	1.2	1.6	1.9	
	90 mm	0,270 ft	-	-	-	-	-	-	0.7	0.9	1.1	1.4	1.7	
	100 mm	0,300 ft	-	-	-	-	-	-	0.6	0.8	1.0	1.3	1.6	
	110 mm	0,330 ft	-	-	-	-	-	-	0.5	0.7	0.9	1.2	1.4	
120 mm	0,360 ft	-	-	-	-	-	-	0.5	0.7	0.8	1.1	1.3		

Consumption of WKT Sealing Compound per running meter joint														
		Measures of the joint												
		Width ▶		4 mm			5 mm			6 mm			8 mm	
				0.012 ft			0.015 ft			0.018 ff			0.024 ft	
Depth ▶				6 mm	8 mm	10 mm	6 mm	8 mm	10 mm	6 mm	8 mm	10 mm	10 mm	12 mm
				0.018 ft	0.024 ft	0.030 ft	0.018 ft	0.024 ft	0.030 ft	0.018 ft	0.024 ft	0.030 ft	0.030 ft	0.030 ft
WKT Sealing Compound per running meter joint ▶			24 ml	32 ml	40 ml	30 ml	40 ml	50 ml	36 ml	48 ml	60 ml	80 ml	96 ml	

Running meter joint per 570 ml cartridge														
		Measures of the joint												
		Width ▶		4 mm			5 mm			6 mm			8 mm	
				0.012 ft			0.015 ft			0.018 ff			0.024 ft	
Depth ▶				6 mm	8 mm	10 mm	6 mm	8 mm	10 mm	6 mm	8 mm	10 mm	10 mm	12 mm
				0.018 ft	0.024 ft	0.030 ft	0.018 ft	0.024 ft	0.030 ft	0.018 ft	0.024 ft	0.030 ft	0.030 ft	0.030 ft
Running meter joint per 570 ml Cartridge ▶			23.7 m	17.8 m	14.2 m	19.0 m	14.2 m	11.4 m	15.8 m	11.9 m	9.5 m	7.1 m	5.9 m	
			77.76 ft	58.40 ft	46.59 ft	62.34 ft	46.59 ft	37.40 ft	51.84 ft	39.04 ft	31.17 ft	23.30 ft	19.36 ft	

Consumption of WKT Primer depends strongly on several factors e.g. way of application, type of wood etc. Therefore, it can only be roughly estimated with approx. 100 ml primer per 570 ml cartridge.

Disclaimer: This list is provided by PREMAPRO LLC to assist you. However, it is a rough calculation only. The exact product amount may differ due to surface and wood conditions and other circumstances that can not be take into account in this schedule. Deviations are possible and are not our responsibility. For more exact numbers, please perform a specific calculation based on your project. All Information listed is without guarantee. The manufacturer reserves the right to make technical and visual changes to this data.